



## Solarcheck Mobilcenter KOMPAKT **NEW**

### Small Size – Great Device

Filling and flushing station for

- solar collectors
- heat pumps
- ground collectors
- panel heating systems




**THE ORIGINAL**  
Made in Germany



## Top end equipment

	<p>✓ <b>telescopic handle</b> <b>NEW</b> adjustable height (78 to 110 cm), comfortable soft grip</p>		<p>✓ <b>wide charging mouth</b> for easy filling and fixing of extra filter bags</p>
	<p>✓ <b>hoses</b> temperature resistant up to 100°C</p>		<p>✓ <b>tank</b> with level indication removable container, exchangeable for different heat transfer fluids</p>
	<p>✓ <b>large inflatable wheels</b> perfectly manoeuvrable on uneven ground, ideal for construction sites</p>		<p>✓ <b>return hose connection</b> <b>NEW</b> 90° angle, no bending of hose. Secured caps!</p>
	<p>✓ <b>powerful impeller pump</b> with filter and pressure relief valve</p>		<p>✓ <b>ball valves</b> <b>NEW</b> on hose ends, no leaking during transport</p>

 <p><b>NEW: carrying handle</b></p>	<p><b>Easy transport</b></p> <ul style="list-style-type: none"> <li>- Carrying handle on rearward side for single handed carrying, stairs or other obstacles cause no problems.</li> <li>- With retracted handle the station fits into the trunk of even small cars (VW Rabbit).</li> <li>- The device is absolutely leak proof, both in horizontal or vertical transport.</li> </ul>	<p><b>Filling without air enclosures</b></p> <ul style="list-style-type: none"> <li>- Ball valves allow pre-filling of hoses. No air from the hoses enters into the solar collectors during filling process.</li> <li>- The transparent filter cup shows whether there is air left in the system.</li> </ul>
--	---	--

## Technical Data

<b>pump</b>	dry self-priming impeller pump with glycol resistant impeller
<b>flow rate / working pressure max.</b>	30 litres per minute / 5 bar
<b>temperature max.</b>	90°C
<b>motor</b>	motors available: 230V/50 Hz, 110V/50 Hz (UK), 110V/60Hz (USA/CAN) with thermal motor protection and 2 metres cable with plug
<b>weight</b>	21 kg (trolley with pump, hoses and empty tank)
<b>packing dimensions</b>	H x W x D = 800 x 400 x 500 mm
<b>tank</b>	UV stabilised PE tank, content 30 litres
<b>trolley</b>	welded, robust chassis made of formed tube
<b>accessories</b>	filter, lid with return hose connection, remote control



**ZUWA-Zumpe GmbH**  
**Pumps and Plant Protection Equipment**  
 Franz-Fuchs-Straße 13 - 17 • D-83410 Laufen  
 phone: +49 8682 89340 • fax: +49 8682 893434  
 e-mail: info@zuwa.de • internet: www.zuwa.de